(19) World Intellectual Property **Organization**

International Bureau



(43) International Publication Date 30 June 2005 (30.06.2005)

PCT

(10) International Publication Number WO 2005/058145 A3

(51) International Patent Classification7:

A61B 5/04

(21) International Application Number:

PCT/US2004/042488

(22) International Filing Date:

17 December 2004 (17.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/530,696

17 December 2003 (17.12.2003)


- (71) Applicant (for all designated States except US): THE RE-GENTS OF THE UNIVERSITY OF COLORADO, A BODY CORPORATE [US/US]; 4001 Discovery Drive, Suite 390 / 588 UCB, Boulder, CO 80309 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VANSICKLE, David, P. [US/US]; 2041 Ivy Street, Denver, CO 80207

(US). WINSTON, Ken, R. [US/US]; 24668 Foothills Drive North, Golden, CO 80401 (US).

- (74) Agent: MACHELEDT, Jean, M.; Macheledt Bales & Heidmiller LLP, 501 Skysail Lane, Suite B100, Fort Collins, CO 80525-3133 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: ACTIVEINVASIVE EEG DEVICE AND TECHNIQUE



(57) Abstract: An electrode device for taking a plurality of EEG measurements, and an associated method of taking EEG measurements, whereby a plurality of electrode contact-points configured atop a support member are in electrical communication with, and in relative proximity to, an integrated circuit comprising converter circuitry adapted for converting analog EEG signals measured, having originated from within a patient, into digital signals prior to transmission thereof to a processing unit. The integrated circuit/circuitry (IC) may be supported by the support member or by a lead assembly having wiring for the digital signal transmission. The support member may have a plurality of layers and be generally flexible; as fabricated of any of a number of flexible, generally insulative biocompatible materials to which circuitry may be etched or deposited, exhibiting sufficient structural integrity to decrease likelihood of degradation during surgery or once implanted.



WO 2005/058145 A3



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- (88) Date of publication of the international search report: 24 November 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.